

SCREW FIT RESERVOIRS



Instructions for fitting CP4709 Screw Type Reservoirs:-

Assembly Part Numbers:-

- CP4709-10 Long
- CP4709-11 Medium
- CP4709-12 Short

Suitable for direct fitment to CP2623, CP4623, CP5623 & CP6093 type Master Cylinders.



Instructions:-



fig 1.

1. Remove and discard inlet adaptor Blue or Gold, and copper gasket fitted to the master cylinder and clean thread. fig 1.

2. Fit O-Ring seal supplied into groove in reservoir base. (fig 2.)



fig 2.



fig 3.

3. Screw reservoir into master cylinder body until the slack is taken up, then hand tighten a further $\frac{1}{2}$ to $\frac{3}{4}$ turn, this is sufficient. (fig 3.)

NOTE: Adaptors are available for remote use, part number details below:-

Follow steps 2 & 3 above to fit.

- CP4709-105 - 7/16" Thread.
- CP4709-106 - M12 Thread.
- CP4709-107 - Push-on-type.

Publication Ref: P14.073/04

AP Racing Ltd,

Wheler Road, Coventry, CV3 4LB, United Kingdom
Tel: +44 (0) 24 7663 9595 Fax: +44 (0) 24 76639559
E-mail: sales@ap racing.co.uk Web: www.ap racing.com